



Helix Plate Sizes	
Diameter (in)	
8	
10	
12	
14	
16	
18	
20	
22	
24	
26	
28	
30	
<i>Note: Other sizes available per project requirements</i>	

NOTES:

1. Ultimate Torque Rating: 16,000 ft-lbs
2. Ultimate Capacity Based on Torque: 144 kips
3. Installation Torque Factor (K_t): 8.0 - 9.0
4. Coupling Bolts: $\varnothing 3/4$ " dia. heavy hex bolt per ASTM A325 (Typ. 3 per Connection)
5. Coating: Hot dip galvanization per ASTM A123/A153 or Bare Steel



VIKING HELICAL ANCHORS
 7615 Smetana Lane, Suite 140
 Eden Prairie, MN 55344
 Office: (800) 733-3801
 Fax: (952) 941-4633
 www.vikinghelicalanchors.com

CLIENT/PROJECT		DRAWING TITLE						
N/A		2.875" OD x 0.276w Helical Pile Lead & Extension Specifications						
THIS DRAWING CONTAINS CONFIDENTIAL INFORMATION OF VIKING HELICAL ANCHORS. THIS DOCUMENT MAY NOT BE REPRODUCED IN ANY FORM WITHOUT THE EXPRESS WRITTEN PERMISSION OF VIKING HELICAL ANCHORS.		PRELIMINARY DESIGN. THIS DRAWING IS MEANT TO SERVE AS AN EXAMPLE ONLY. NOT ISSUED FOR CONSTRUCTION.		SCALE	DRAWING NUMBER	REV.	AUTHOR	DATE
		NTS		VHA-101820163	1.0	TJH	10/18/2016	